

ADVANTECH EQUIPMENT CORP.

7F, No. 98, Ming-Chuan Road, Shing-Tien City, Taipei, Taiwan, R. O. C. TEL: 886-2-2218-2325; FAX: 886-2-2218-2435

Home Page: http://www.aec.com.tw

List of LabTool-S100 Serial Flash Programmer and Adapter

1. Delivery: contact AEC for actual lead time.

2. Payment: T/T in Advance

P/N

3. Term: FOB USD Taiwan. All price are subject to change without notice.

Description

4. Order amount under USD200 will be charged USD15 for special handling fee.

Oct, 2020

Package

sed Serial Flash Prog		
LabTool-S100	PC based Serial Flash Programmer with USB interface	
	Include 8-16 pin SOIC 150mil (1.27mm pitch) adapter	
	Support OS: Windows XP/Vista/7/8.1/10 •	
Flash (25 Series) ad	apter for LabTool-S100 PC based Serial Flash Programmer	
ADP-DIP-001	Adapter for 8 pin DIP Serial Flash (25 Series) (DIP Socket)	8 DIP/p2.54m
ADP-EBGA-2401M	Adapter for 24 pin EBGA, 6mm x 8mm, 1.0 mm pitch with 6x4	24EBGA/p1.0m
	ball matrix Serial Flash (25 Series) (Open-Top Socket)	Body Size: 6
		Matrix: 4:
ADP-EBGA-2402M	Adapter for 24 pin EBGA, 6mm x 8mm, 1.0 mm pitch with 5x5	24EBGA/p1.0n
	ball matrix Serial Flash (25 Series) (Open-Top Socket)	Body Size: 6
		Matrix: 5
ADP-EBGA-2404	Adapter for 24 pin EBGA, 6mm x 8mm, 1.0 mm pitch with 5x5	24EBGA/p1.0n
	ball matrix Macronix MX25UM51245G (Open-Top Socket)	Body Size: 6
		Matrix: 5
ADP-QFN-0801	Adapter for 8 pin QFN (WSON) 5mm x 6mm with 1.27mm pitch	8WSON/p1.27n
	Serial Flash (25 Series) (Open-Top Socket)	Body Size : 5
ADP-QFN-0802	Adapter for 8 pin QFN (WSON) 6mm x 8mm with 1.27mm pitch	8WSON/p1.27n
	Serial Flash (25 Series) (Clam-Shell Socket)	Body Size : 6
ADP-QFN-0803	Adapter for 8 pin QFN (WSON) 2mm x 3mm with 0.5mm pitch	8USON/p0.5n
ADP-QFN-0804	Serial Flash (25 Series) (Clam-Shell Socket) Adapter for 8 pin QFN (WSON) 4mm x 4mm with 0.8mm pitch	Body Size: 2 8USON/p0.8n
	Serial Flash (25 Series) (Open-Top Socket)	Body Size : 4
ADP-QFN-0806	Adapter for 8 pin QFN (WSON) 3mm x 4mm with 0.8mm pitch	8USON/p0.8n
	Serial Flash (25 Series) (Clam-Shell Socket)	Body Size : 3
ADP-SOIC-1601	Adapter for 8 pin 150 mil SOIC, 1.27mm pitch Serial Flash (25	8SOIC/p1.27n
	Series) (Open-Top Socket)	Body Width 150
ADP-SOIC-2001	Adapter for 8 pin 208 mil SOIC, 1.27mm pitch Serial Flash (25	8SOIC/p1.27n
	Series) (Open-Top Socket)	Body Width 200
ADP-SOIC-2801	Adapter for 16 pin 300 mil SOIC, 1.27mm pitch Serial Flash (25	16SOIC/p1.27n
	Series) (Open-Top Socket)	Body Width 300r
ADP-SOIC-2801C	Adapter for 16 pin 300 mil SOIC, 1.27mm pitch Serial Flash (25	16SOIC/p1.27n
	Series) (Clam-Shell Socket)	Body Width 300r
ADP-TSSOP-1601	Adapter for 8 pin 173mil TSSOP, 0.65mm pitch Serial Flash (25	8TSSOP/p0.65n
		5 1 MARIE :=5

Series) (Clam-Shell Socket)

Body Width 173mil

P/	'N	Description	Package		
AΓ	DP-TSSOP-2801	Adapter for 8 pin 173mil TSSOP, 0.65mm pitch Serial Flash (25 Series) (Open-Top Socket)	8TSSOP/p0.65mm Body Width 173mil		
<u> 12C Seria</u>	I2C Serial EEPROM (24 Series) adapter for LabTool-S100 PC based Serial Flash Programmer				
AΓ	OP-DIP-002	Adapter for 8 pin DIP I2C Serial EEPROM (24 Series) (DIP Socket)	8 DIP/p2.54mm		
ΑI	OP-MSOP-0801	Adapter for 8 pin MSOP Body Width 3mm, Tip To Tip Width	8MSOP/p0.65mm		
		4.9mm with 0.65mm pitch I2C Serial EEPROM (24 Series) (Clam- Shell Socket)	Body Width 3mm		
AΓ	OP-QFN-0808	Adapter for 8 pin QFN (WSON) 2mm x 3mm with 0.5mm pitch	8USON/p0.5mm		
		I2C Serial EEPROM (24 Series) (Clam-Shell Socket)	Body Size: 2x3		
ADP-QFN-0809	OP-QFN-0809	Adapter for 8 pin QFN (WSON) 5mm x 6mm with 1.27mm pitch	8WSON/p1.27mm		
		I2C Serial EEPROM (24 Series) (Open-Top Socket)	Body Size: 5 x 6		
ΑI	OP-SOIC-1602	Adapter for 8 pin 150 mil SOIC, 1.27mm pitch I2C Serial	8SOIC/p1.27mm		
		EEPROM (24 Series) (Open-Top Socket)	Body Width 150mil		
AΓ	OP-SOIC-2002	Adapter for 8 pin 208 mil SOIC, 1.27mm pitch I2C Serial	8SOIC/p1.27mm		
		EEPROM (24 Series) (Open-Top Socket)	Body Width 200mil		
AL	DP-TSSOP-1602	Adapter for 8 pin 173mil TSSOP, 0.65mm pitch I2C Serial EEPROM (24 Series) (Clam-Shell Socket)	8TSSOP/p0.65mm Body Width 173mil		
		EEPROM (24 Series) (Clain-Shell Socket)	body width 173iiil		
	Serial EEPROM (93 Series) adapter for LabTool-S100 PC based Serial Flash Programmer				
ΑI	OP-DIP-003	Adapter for 8 pin DIP Serial EEPROM (93 Series) (DIP Socket)	8 DIP/p2.54mm		
ΑI	OP-SOIC-1603	Adapter for 8 pin 150 mil SOIC, 1.27mm pitch Serial EEPROM	8SOIC/p1.27mm		
_		(93 Series) (Open-Top Socket)	Body Width 150mil		
ΑI	OP-SOIC-2003	Adapter for 8 pin 208 mil SOIC, 1.27mm pitch Serial EEPROM	8SOIC/p1.27mm		
		(93 Series) (Open-Top Socket)	Body Width 200mil		
ΑI	DP-TSSOP-1603	Adapter for 8 pin 173mil TSSOP, 0.65mm pitch Serial EEPROM	8TSSOP/p0.65mm		
_		(93 Series) (Clam-Shell Socket)	Body Width 173mil		
AΓ	OP-QFN-0810	Adapter for 8 pin QFN (WSON) 2mm x 3mm with 0.5mm pitch	8USON/p0.5mm		
		Serial EEPROM (93 Series) (Clam-Shell Socket)	Body Size: 2x3		