

ADVANTECH EQUIPMENT CORP.

7F, No. 98, Ming-Chuan Road, Shing-Tien City, Taipei, Taiwan, R. O. C. TEL: 886-2-2218-2325; FAX: 886-2-2218-2435

Home Page: http://www.aec.com.tw

List of LabTool-S100 Serial Flash Programmer and Adapter

1. Delivery: contact AEC for actual lead time.

2. Payment: T/T in Advance

- 3. Term: FOB USD Taiwan. All price are subject to change without notice.
- 4. Order amount under USD200 will be charged USD15 for special handling fee.

Jan. 2021

			Juli, 2021			
	P/N	Description	Package			
PC based Serial Flash Programmer						
	LabTool-S100	PC based Serial Flash Programmer with USB interface Include 8-16 pin SOIC 150mil (1.27mm pitch) adapter Support OS: Windows XP/Vista/7/8.1/10 •				
Serial Flash (25 Series) adapter for LabTool-S100 PC based Serial Flash Programmer						
	ADP-DIP-001	Adapter for 8 pin DIP Serial Flash (25 Series) (DIP Socket)	8 DIP/p2.54mm			
	ADP-EBGA-2401M	Adapter for 24 pin EBGA, 6mm x 8mm, 1.0 mm pitch with 6x4 ball matrix Serial Flash (25 Series) (Open-Top Socket)	24EBGA/p1.0mm Body Size: 6 x 8 Matrix: 4 x 6			

ADP-EBGA-2401M	Adapter for 24 pin EBGA, 6mm x 8mm, 1.0 mm pitch with 6x4 ball matrix Serial Flash (25 Series) (Open-Top Socket)	24EBGA/p1.0mm Body Size:6 x 8 Matrix:4 x 6
ADP-EBGA-2402M	Adapter for 24 pin EBGA, 6mm x 8mm, 1.0 mm pitch with 5x5 ball matrix Serial Flash (25 Series) (Open-Top Socket)	24EBGA/p1.0mm Body Size: 6 x 8 Matrix: 5 x 5
ADP-EBGA-2404	Adapter for 24 pin EBGA, 6mm x 8mm, 1.0 mm pitch with 5x5 ball matrix Macronix MX25UM51245G (Open-Top Socket)	24EBGA/p1.0mm Body Size:6 x 8 Matrix:5 x 5
ADP-QFN-0801	Adapter for 8 pin QFN (WSON) 5mm x 6mm with 1.27mm pitch Serial Flash (25 Series) (Open-Top Socket)	8WSON/p1.27mm Body Size : 5×6
ADP-QFN-0802	Adapter for 8 pin QFN (WSON) 6mm x 8mm with 1.27mm pitch Serial Flash (25 Series) (Clam-Shell Socket)	8WSON/p1.27mm Body Size: 6 x 8
ADP-QFN-0803	Adapter for 8 pin QFN (WSON) 2mm x 3mm with 0.5mm pitch Serial Flash (25 Series) (Clam-Shell Socket)	8USON/p0.5mm Body Size:2x3
ADP-QFN-0804	Adapter for 8 pin QFN (WSON) 4mm x 4mm with 0.8mm pitch Serial Flash (25 Series) (Open-Top Socket)	8USON/p0.8mm Body Size: 4 x 4
ADP-QFN-0806	Adapter for 8 pin QFN (WSON) 3mm x 4mm with 0.8mm pitch Serial Flash (25 Series) (Clam-Shell Socket)	8USON/p0.8mm Body Size: 3 x 4
ADP-SOIC-1601	Adapter for 8 pin 150 mil SOIC, 1.27mm pitch Serial Flash (25 Series) (Open-Top Socket)	8SOIC/p1.27mm Body Width 150mil
ADP-SOIC-2001	Adapter for 8 pin 208 mil SOIC, 1.27mm pitch Serial Flash (25 Series) (Open-Top Socket)	8SOIC/p1.27mm Body Width 200mil
ADP-SOIC-2801	Adapter for 16 pin 300 mil SOIC, 1.27mm pitch Serial Flash (25 Series) (Open-Top Socket)	16SOIC/p1.27mm Body Width 300mil
ADP-SOIC-2801C	Adapter for 16 pin 300 mil SOIC, 1.27mm pitch Serial Flash (25 Series) (Clam-Shell Socket)	16SOIC/p1.27mm Body Width 300mil
ADP-TSSOP-1601	Adapter for 8 pin 173mil TSSOP, 0.65mm pitch Serial Flash (25 Series) (Clam-Shell Socket)	8TSSOP/p0.65mm Body Width 173mil

P/N		Description	Package			
ADP-TS	SSOP-2801	Adapter for 8 pin 173mil TSSOP, 0.65mm pitch Serial Flash (25	8TSSOP/p0.65mm			
		Series) (Open-Top Socket)	Body Width 173mil			
I2C Serial EEPROM (24 Series) adapter for LabTool-S100 PC based Serial Flash Programmer						
ADP-DI	P-002	Adapter for 8 pin DIP I2C Serial EEPROM (24 Series) (DIP Socket)	8 DIP/p2.54mm			
ADP-M	SOP-0801	Adapter for 8 pin MSOP Body Width 3mm, Tip To Tip Width	8MSOP/p0.65mm			
		4.9mm with 0.65mm pitch I2C Serial EEPROM (24 Series) (Clam- Shell Socket)	Body Width 3mm			
ADP-Q	FN-0808	Adapter for 8 pin QFN (WSON) 2mm x 3mm with 0.5mm pitch	8USON/p0.5mm			
		I2C Serial EEPROM (24 Series) (Clam-Shell Socket)	Body Size: 2x3			
ADP-Q	FN-0809	Adapter for 8 pin QFN (WSON) 5mm x 6mm with 1.27mm pitch	8WSON/p1.27mm			
		I2C Serial EEPROM (24 Series) (Open-Top Socket)	Body Size: 5 x 6			
ADP-SO	DIC-1602	Adapter for 8 pin 150 mil SOIC, 1.27mm pitch I2C Serial	8SOIC/p1.27mm			
		EEPROM (24 Series) (Open-Top Socket)	Body Width 150mil			
ADP-SC	DIC-2002	Adapter for 8 pin 208 mil SOIC, 1.27mm pitch I2C Serial	8SOIC/p1.27mm			
		EEPROM (24 Series) (Open-Top Socket)	Body Width 200mil			
ADP-TS	SSOP-1602	Adapter for 8 pin 173mil TSSOP, 0.65mm pitch I2C Serial	8TSSOP/p0.65mm			
		EEPROM (24 Series) (Clam-Shell Socket)	Body Width 173mil			
<u>Serial EEPRO</u>	M (93 Series)	adapter for LabTool-S100 PC based Serial Flash Programmer				
ADP-DI	P-003	Adapter for 8 pin DIP Serial EEPROM (93 Series) (DIP Socket)	8 DIP/p2.54mm			
ADP-SC	DIC-1603	Adapter for 8 pin 150 mil SOIC, 1.27mm pitch Serial EEPROM	8SOIC/p1.27mm			
		(93 Series) (Open-Top Socket)	Body Width 150mil			
ADP-SC	DIC-2003	Adapter for 8 pin 208 mil SOIC, 1.27mm pitch Serial EEPROM	8SOIC/p1.27mm			
		(93 Series) (Open-Top Socket)	Body Width 200mil			
ADP-TS	SSOP-1603	Adapter for 8 pin 173mil TSSOP, 0.65mm pitch Serial EEPROM	8TSSOP/p0.65mm			
		(93 Series) (Clam-Shell Socket)	Body Width 173mil			
ADP-Q	FN-0810	Adapter for 8 pin QFN (WSON) 2mm x 3mm with 0.5mm pitch	8USON/p0.5mm			
		Serial EEPROM (93 Series) (Clam-Shell Socket)	Body Size: 2x3			