

List of LabTool-S100 Serial Flash Programmer and Adapter

1. Delivery : contact AEC for actual lead time.
2. Payment : T/T in Advance
3. Term : FOB USD Taiwan. All price are subject to change without notice.
4. Order amount under USD200 will be charged USD15 for special handling fee.

Oct, 2021

| P/N | Description | Package |
|--|--|--|
| <u>PC based Serial Flash Programmer</u> | | |
| LabTool-S100 | PC based Serial Flash Programmer with USB interface Include 8-16 pin SOIC 150mil (1.27mm pitch) adapter Support OS : Windows XP/Vista/7/8.1/10 ° | |
| <u>Serial Flash (25 Series) adapter for LabTool-S100 PC based Serial Flash Programmer</u> | | |
| ADP-DIP-001 | Adapter for 8 pin DIP Serial Flash (25 Series) (DIP Socket) | 8 DIP/p2.54mm |
| ADP-EBGA-2401M | Adapter for 24 pin EBGA, 6mm x 8mm, 1.0 mm pitch with 6x4 ball matrix Serial Flash (25 Series) (Open-Top Socket) | 24EBGA/p1.0mm Body Size : 6 x 8 Matrix : 4 x 6 |
| ADP-EBGA-2402M | Adapter for 24 pin EBGA, 6mm x 8mm, 1.0 mm pitch with 5x5 ball matrix Serial Flash (25 Series) (Open-Top Socket) | 24EBGA/p1.0mm Body Size : 6 x 8 Matrix : 5 x 5 |
| ADP-EBGA-2404 | Adapter for 24 pin EBGA, 6mm x 8mm, 1.0 mm pitch with 5x5 ball matrix Macronix MX25UM51245G (Open-Top Socket) | 24EBGA/p1.0mm Body Size : 6 x 8 Matrix : 5 x 5 |
| ADP-QFN-0801 | Adapter for 8 pin QFN (WSON) 5mm x 6mm with 1.27mm pitch Serial Flash (25 Series) (Open-Top Socket) | 8WSON/p1.27mm Body Size : 5 x 6 |
| ADP-QFN-0802 | Adapter for 8 pin QFN (WSON) 6mm x 8mm with 1.27mm pitch Serial Flash (25 Series) (Clam-Shell Socket) | 8WSON/p1.27mm Body Size : 6 x 8 |
| ADP-QFN-0803 | Adapter for 8 pin QFN (WSON) 2mm x 3mm with 0.5mm pitch Serial Flash (25 Series) (Clam-Shell Socket) | 8USON/p0.5mm Body Size : 2x3 |
| ADP-QFN-0804 | Adapter for 8 pin QFN (WSON) 4mm x 4mm with 0.8mm pitch Serial Flash (25 Series) (Open-Top Socket) | 8USON/p0.8mm Body Size : 4 x 4 |
| ADP-QFN-0806 | Adapter for 8 pin QFN (WSON) 3mm x 4mm with 0.8mm pitch Serial Flash (25 Series) (Clam-Shell Socket) | 8USON/p0.8mm Body Size : 3 x 4 |
| ADP-SOIC-1601 | Adapter for 8 pin 150 mil SOIC, 1.27mm pitch Serial Flash (25 Series) (Open-Top Socket) | 8SOIC/p1.27mm Body Width 150mil |
| ADP-SOIC-2001 | Adapter for 8 pin 208 mil SOIC, 1.27mm pitch Serial Flash (25 Series) (Open-Top Socket) | 8SOIC/p1.27mm Body Width 200mil |
| ADP-SOIC-2801 | Adapter for 16 pin 300 mil SOIC, 1.27mm pitch Serial Flash (25 Series) (Open-Top Socket) | 16SOIC/p1.27mm Body Width 300mil |
| ADP-SOIC-2801C | Adapter for 16 pin 300 mil SOIC, 1.27mm pitch Serial Flash (25 Series) (Clam-Shell Socket) | 16SOIC/p1.27mm Body Width 300mil |
| ADP-TSSOP-1601 | Adapter for 8 pin 173mil TSSOP, 0.65mm pitch Serial Flash (25 Series) (Clam-Shell Socket) | 8TSSOP/p0.65mm Body Width 173mil |

| P/N | Description | Package |
|----------------|---|-------------------------------------|
| ADP-TSSOP-2801 | Adapter for 8 pin 173mil TSSOP, 0.65mm pitch Serial Flash (25 Series) (Open-Top Socket) | 8TSSOP/p0.65mm Body Width 173mil |

[I2C Serial EEPROM \(24 Series\) adapter for LabTool-S100 PC based Serial Flash Programmer](#)

| | | |
|----------------|---|-------------------------------------|
| ADP-DIP-002 | Adapter for 8 pin DIP I2C Serial EEPROM (24 Series) (DIP Socket) | 8 DIP/p2.54mm |
| ADP-MSOP-0801 | Adapter for 8 pin MSOP Body Width 3mm, Tip To Tip Width 4.9mm with 0.65mm pitch I2C Serial EEPROM (24 Series) (Clam-Shell Socket) | 8MSOP/p0.65mm Body Width 3mm |
| ADP-QFN-0808 | Adapter for 8 pin QFN (WSON) 2mm x 3mm with 0.5mm pitch I2C Serial EEPROM (24 Series) (Clam-Shell Socket) | 8USON/p0.5mm Body Size : 2x3 |
| ADP-QFN-0809 | Adapter for 8 pin QFN (WSON) 5mm x 6mm with 1.27mm pitch I2C Serial EEPROM (24 Series) (Open-Top Socket) | 8WSON/p1.27mm Body Size : 5 x 6 |
| ADP-SOIC-1602 | Adapter for 8 pin 150 mil SOIC, 1.27mm pitch I2C Serial EEPROM (24 Series) (Open-Top Socket) | 8SOIC/p1.27mm Body Width 150mil |
| ADP-SOIC-2002 | Adapter for 8 pin 208 mil SOIC, 1.27mm pitch I2C Serial EEPROM (24 Series) (Open-Top Socket) | 8SOIC/p1.27mm Body Width 200mil |
| ADP-TSSOP-1602 | Adapter for 8 pin 173mil TSSOP, 0.65mm pitch I2C Serial EEPROM (24 Series) (Clam-Shell Socket) | 8TSSOP/p0.65mm Body Width 173mil |

[Serial EEPROM \(93 Series\) adapter for LabTool-S100 PC based Serial Flash Programmer](#)

| | | |
|----------------|---|-------------------------------------|
| ADP-DIP-003 | Adapter for 8 pin DIP Serial EEPROM (93 Series) (DIP Socket) | 8 DIP/p2.54mm |
| ADP-SOIC-1603 | Adapter for 8 pin 150 mil SOIC, 1.27mm pitch Serial EEPROM (93 Series) (Open-Top Socket) | 8SOIC/p1.27mm Body Width 150mil |
| ADP-SOIC-2003 | Adapter for 8 pin 208 mil SOIC, 1.27mm pitch Serial EEPROM (93 Series) (Open-Top Socket) | 8SOIC/p1.27mm Body Width 200mil |
| ADP-TSSOP-1603 | Adapter for 8 pin 173mil TSSOP, 0.65mm pitch Serial EEPROM (93 Series) (Clam-Shell Socket) | 8TSSOP/p0.65mm Body Width 173mil |
| ADP-QFN-0810 | Adapter for 8 pin QFN (WSON) 2mm x 3mm with 0.5mm pitch Serial EEPROM (93 Series) (Clam-Shell Socket) | 8USON/p0.5mm Body Size : 2x3 |